

HFO-1234yf REFRIGERANT CHEMICALS & TOOLS...



U/V LEAK DETECTION SUPER DYE

- SAE Certified for HFO-1234vf A/C Systems
- Safe for hybrid and electric A/C systems
- Compatible with PAG, ester & mineral oils
- Does not contain solvents, will not harm A/C systems or recovery equipment
- Contains anti-wear agents, friction modifiers and anti-oxidants.
- 1/4 oz. (7.5 ml) per vehicle

Part # 24056 Super Dye self-measure bottle 16 oz. (473 ml) Part # 22816 Super Dye self-measure bottle 8 oz. (237 ml) Part # 33003 Super Dye round bottle 1 oz. (29.5 ml)



HF01234vf **CHARGING HOSE**


- Screw on can tap hose for sealing 12 oz. cans of HFO-1234yf
- 90° Low side quick coupler
- Easy to read gauge

HFO-1234yf Charging Hose & Gauge

INCLUDED

ALUMINUM MANIFOLD GAUGE WITH HOSES

- For use with HFO-1234yf refrigerant
- Includes 72" hoses, red, blue, yellow & lock-on service couplers in plastic case
- Scales in PSI & BAR
- Large sight glass
- **Auxiliary vacuum** line access port





Part # 26890

HF0-1234vf Low Side Coupler

Part # 26906 HF0-1234vf High Side

Coupler



Part # 50130 HFO-1234yf Tank Adapter



Vacuum Pump Adapter





HFO-1234vf REFRIGERANT

Low GWP, zero ODP refrigerant which meets EU F-gas regulation • Thermally stable under extreme conditions • Comparable energy efficiency & capacity to R-134a • Cost-effective, replacement for R-134a

Part # HF0-1234yf-10 Dupont 10 lb. Cylinder Part # 1302 Honeywell 8 oz. Service Can / 4 per case



HF01234yf CAN TAP

 Brass dispensing valve for self-sealing HF01234vf cans with 1/2" ACME LH fitting

Part # 52059 HF0-1234vf Can Tap



HFO-1234vf PAG LUBRICA

Synthetic PAG for systems using HF0-1234vf refrigerant • Excellent resistance to moisture, lubricity & compressor protection. • Contains conditioners, inhibitors & anti-wear agents

PAG 46-H Without Dve 8 oz. Part # 27262 Part # 42432 PAG 46-H Without Dve 32 oz. Part # 38589 PAG 100-H Without Dye 8 oz. Part # 42449 PAG 100-H Without Dye 32 oz.

Part # 64861 1234yf POE Hybrid & Electric 4 oz.

PAG 46-H + U/V Dye 8 oz. Part # 27262D Part # 42432D PAG 46-H + U/V Dye 32 oz. Part # 38589D PAG 100-H + U/V Dye 8 oz. Part # 42449D PAG 100-H + U/V Dye 32 oz.



UNIVERSAL 68 LUBRICANT

Multi-Grade oil Compatible with A/C systems using HF0-1234yf or R-134a refrigerant. . Safe for hybrid & electric compressors. Complete additive package.

Part # 48663-32 Universal 68 Without Dye 32 oz. Part # 48663-32D Universal 68 + UV Dve 32 oz.



TOTAL LEAK STOP + U/V DYE

- · Stops small leaks in evaporators, condensers, hoses, gaskets, seals & 0-rings
- · Does not contain polymers. Will not harm or clog A/C system components or equipment.
- Installs easily using an oil injector

Part # 39241-YF Part # 39241B-YF

Total Leak Stop with U/V Dye 1oz. (28.5 g) Total Leak Stop with U/V Dye 1oz. (28.5 g)

Part # ST22 Total Leak Stop + U/V Dye 2 oz. bottle

A/C FLASH FLUSH

- Leaves no residue Effective cleaner
- Quickly penetrates and removes oil & other contaminants
- Non-corrosive

Part # 22762 Flash Flush Quart Flash Flush Gallon Part # 22779

A/C FLUSH GUN

- Compressed Air Hose Adaptor Included
- Attach to shop air
- Ideal for removing contaminants, moisture, and acid from A/C systems
- **Detailed instructions** included





VC FLASH

FLUSH



HAND-TURN DYE/OIL INJECTOR

- Does not require a Manifold Gauge to use on low side of pressurized systems
- · Great for introducing from 1/4oz. (7.5ml) up to 2oz. (60ml) of U/V Dye, Lubricants and Leak Stop to a closed A/C system without adding refrigerant
- Quick connect style for HFO-1234vf systems

Part # 43460 HFO-1234vf Hand Turn Injector