

AC & REFRIGERATION SYSTEM LEAK STOP Made Easy!

**PATENTED HFC FREE
AEROSOL DELIVERY SYSTEM!**



**SELF-CONTAINED SYSTEM
NO SPECIAL TOOLS REQUIRED!**



**Compatible With All
Oils And Refrigerant**



**Screw-on connector
for HVAC systems**



**HFC
FREE
AEROSOL**



**R410a ADAPTER
Available**

HVAC LEAK STOP + U/V DYE

- Permanently seals leaks in A/C & refrigeration systems
- Safe for all HVAC units, does not contain polymers
- Stops leaks in metal and rubber air conditioner and refrigeration parts including evaporators, O-rings, gaskets and hoses
- Lubricates air conditioning and refrigeration compressors
- Includes O-ring conditioner, proprietary anti-wear & anti-oxidant additives.
- Contains U/V Dye to pinpoint leaks

**Part # 28320B HVAC Leak Stop + U/V Dye 1 oz. (28.5 g)
SMALL SYSTEMS UP TO 1.5 TONS (5.3 KW)**

**Part # 28337B HVAC Leak Stop + U/V Dye 3 oz. (85.5 g)
LARGE SYSTEMS 1.5 - 6 TONS (5.3 - 21.1 KW)**

Part# 51047 R410a Adapter

EASY TO USE

- Shut off system at breaker
- Locate low side service port
- Connect can to A/C system low side service port and inject product into system
- Charge system with refrigerant. (Consult appropriate service manual for proper amount)
- Leak Stop circulates and stops leaks within 30 - 45 minutes of normal A/C system operation

NOTE: For R410a applications, put system in a shallow vacuum to reduce low side pressure prior to installation.

That's all there is to it!

US Patent No. 8,074,009, other US and foreign patents.

TSI Supercool • 3574 Corona St. • Lake Worth, Florida • 33461
www.supercool.ac • 561 - 582 - 2245 • email: sales@supercool.ac • Fax: 561 - 582 - 1499